



OVERVIEW (ENG)

DS03LX



PUSHBUTTON INTERFACE

For connecting your pushbutton switches. Free choice of brand or model. Feedback LEDs can also be connected to this

DS03LXD



PUSHBUTTON INTERFACE DIN

For connecting your pushbutton switches. DIN rail mounting. No feedback LEDs possible.

DS01P



IN GENERAL

BUS TERMINATION

Once required per installation for the correct operation of the Luxom BUS. If DS65L and/or DS41L are already present, then DS01P module is not necessary

DS65L



IP interface

Allows you to connect your Luxom installation to your router. That way, you can configure the installation and have visual display function with iPad, iPhone, windows or Android tablet or device.

DS32L



RS232 interface

For connecting RS232 devices to the Luxom BUS.

CONTROLLERS

DS04L



Relay module

For connecting 4 lighting circuits and 5 switches. Everything is freely configurable. Is mainly used in hotel rooms (1 module per room).

DS08L



For connecting 8 lighting circuits, expandable by 4 by means of an add-on module.

DS10C-CL



Motor + relay controller

For controlling 6 motors or 12 lighting circuits, or a combination of the two. Always by means of the appropriate add-on modules. Five switch inputs and 10 clock functions are present on the module

DS20C



Dimmer + relay controller 0-10V

For controlling 12 0-10V dimmers or 12 lighting circuits, or a combination of the two. Always by means of the appropriate dimmers or add-on modules. Five switch inputs and 2 analog inputs (light measurement) are present on the module


DS20CD



Dimmer controller DMX

For controlling 12 dimmers DMX or 12 lighting circuits, or a combination of the two. Always by means of the appropriate dimmers or add-on modules. Five switch inputs and 2 analog inputs (light measurement) are present on the module

DS02A



Relay 2-channel

For local switching of 2 lights, low power (e.g. LED)

DS04A



Relay 4-channel
For switching 4 lights. To be connected to controller modules.

DS18A



Relay 8-channel
For switching 2x4 lights. To be connected to controller modules.

DS24A



Relay 4-channel
For switching 4 bipolar lights. To be connected to controller modules.

DS30A



DC motors
For connecting to 6 DC motors (e.g. curtains).

DS34A



AC motors
For connecting to 6 AC motors (e.g. shutters).
With hardware protection against simultaneous switching of up and down relay.

DS44A



Fluorescent interface
Converter of 0-10V voltage control to 1-10V current control. For controlling FLUORESCENT fixtures. With 4 relays to switch off the load at low control voltage (to be set)

DIMMING

DS704A



4-channel 0-10V dimmer. Suitable for lamps, motors and LED lighting

DS707A



1-channel LED dimmer, 0-10V control. With built-in supply transformer

DS806A



LED RGB dimmer (3 channels) with DMX control

DS808A



4-channel dimmer DMX. Suitable for lighting

POWER SUPPLIES

DS24P



System power supply 24V / 1A

DS60P



System power supply 24V / 2,5A


DS96P



System power supply 24V / 4A

MOTION

LU0400



24V motion detection with internal LED lighting.
To be connected to a module input (DS03LX, ...)

LU0401



Mounting ring for LU0400 in ceiling


LIGHT DETECTOR

LU0205



0-10V light detector for outdoor installation


VERWARMING
DS30L



HEATING

Thermostat installation. LU3000 sensor included

LU3000



LU3000 temperature sensor

DS30LL



Thermostat with LCD display and function keys.
Temp sensor included

GUI interface

LHC



LUXOM HOME CENTER - plug&play module for controlling a Luxom installation. Automatic recognition of the modules. For OS (iPOD, iPAD, iPHONE), Android, Windows, ... In combination with DS65L IP module.